



MFPS Fiber Optic panel, 19 inch, 1RU, 96 fibers/HU, patch/patch, left, 96 LC/APC, grade C

- Compatible with most common cable types: loose tube, central core, slotted core
- Suitable for cabinets and POP locations
- Various available panel heights to support termination counts from 12 to 288
- Simple wrap-around design for easy fiber routing
- Supports pigtail diameters of 1.2 to 2.4 mm

Product Classification

Product Series	MFPS
Product Type	Fiber patch panel
Regional Availability	EMEA

Construction Materials

Fiber Mode	Singlemode
Fiber Type	G.657.A1
Finish	Powder coated
Material Type	Ethylene-propylene (EP) Polyethylene terephthalate (PET)

Dimensions

Depth	279.91 mm 11.02 in
Height	44.45 mm 1.75 in
Width	482.60 mm 19.00 in

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Temperature	-20 °C to +85 °C (-4 °F to +176 °F)

General Specifications

Rack Units	1.0
Shelf Movement	Hinged
Color	Gray
Color, front	Gray
Door Type, front	Compression latch Hinged
Functionality	Patching
Includes	Mounting hardware
Interface Feature, front	APC

Interface, front	LC
Package Quantity	1
Rack Type	EIA 19 in
Total Ports, quantity	96
Transmission Standards	ETSI EN 300 019-1-3 IEC 61300-3-30

Mechanical Specifications

Cable Exit Location	Side
Patch Cord Entry Location	Front, left side

Optical Performance

Performance Grade	Standard C grade
--------------------------	------------------

Outline Drawing

MFPS Capacities		48		72	96
Connector Type		SC	LC	LC	LC Adapter Pack
19 inch	1HU	48	48	72	96
	2HU	96	96	144	192
	3HU	144	144	216	288

Outline Drawing Used as an image placeholder

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU
ISO 9001:2008

Classification

Compliant
Compliant