# 760238993 | FIST-SOSA2-4SHD-S



FIST<sup>TM</sup> Splice Sub-assembly kit for GCO2-FC/FD flat closures with 4 slim High Density (HD) element trays, each for holding up to 24 primary coated fibers, with Heat Shrink type splice holder

- Splice sub-assemblies consists of a wraparound groove plate holding the included splice organizer trays
- Groove plates are designed with slots for routing fiber to and from the organizer trays
- Loop-back facility allowing for single circuit uncut looped fiber storage on the splice tray
- Compatible with G652.D optical fiber

### **Product Classification**

Product TypeFiber splice trayProduct SeriesFIST-SOSA2Regional AvailabilityEMEAProduct BrandFIST™

### General Specifications

**Application** For use with FIST-GCO2 flat fiber closures

**Color** Gray

Fiber Storage Length, maximum1000 mm for 250 μm fibersFiber Storage Length, minimum750.00 mm | 29.53 in

Package, quantity

Packaging TypeBag| CartonSplice Protector Diameter, maximum2.80 mm| 0.11 inSplice Protector Diameter, minimum2.20 mm| 0.09 inSplice Protector Length, maximum45.00 mm| 1.77 inSplice Protector Length, minimum30.00 mm| 1.18 in

Splice Tray Chip Type Heat shrink

**Splice Tray Construction** SHD (for up to 24 primary coated fibers)

Splice Tray Included, quantity 4

**Splices per Tray, note** 24 splices (250µm) per tray

Splices per Tray, quantity 24
Used UMS Units, quantity 1

#### **Dimensions**

 Height
 4.00 mm | 0.16 in

 Length
 208.00 mm | 8.19 in

 Weight
 0.14 kg | 0.31 lb

 Width
 106.00 mm | 4.17 in

page 1 of 2 November 23, 2018



# 760238993 | FIST-SOSA2-4SHD-S

### Dimension Drawing

**Dimension Drawing** Used as an image placeholder

# Mechanical Specifications

Material Type PC/ABS

Minimum Bend Radius, standard 20.00 mm | 0.79 in

## **Environmental Specifications**

**Environmental Space** Indoor | Outdoor **Relative Humidity** 93%, non-condensing

**Storage Temperature**  $-40 \,^{\circ}\text{C}$  to  $+70 \,^{\circ}\text{C}$  (-40  $^{\circ}\text{F}$  to  $+158 \,^{\circ}\text{F}$ )

## Regulatory Compliance/Certifications

AgencyClassificationRoHS 2011/65/EUCompliant

Used UMS Units, quantity The overal used splice tray height is expressed in UMS units. One UMS unit equals 6 mm.



page 2 of 2

<sup>\*</sup> Footnotes