



FIST™ Splice/patch Sub-assembly kit with 2 trays, each for holding up to 2 fiber adapters and 8 splice protectors

- Splice sub-assemblies consists of a wraparound groove plate holding the included splice organizer trays
- Groove plates are designed with slots for routing fiber to and from the organizer trays

Product Classification

Product Type

Fiber splice/patch tray

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

General Specifications

Application

For use with FIST MK2 organizers

Color

Gray

Fiber Storage Length, maximum

800 mm for mixed 250/900 μ m fibers

Fiber Storage Length, minimum

650.00 mm | 25.59 in

Package, quantity

1

Packaging Type

Bag

Splice Protector Diameter, maximum

2.80 mm | 0.11 in

Splice Protector Diameter, minimum

2.80 mm | 0.11 in

Splice Protector Length, maximum

45.00 mm | 1.77 in

Splice Protector Length, minimum

45.00 mm | 1.77 in

Splice Tray Chip Type

Heat shrink

Splice Tray Construction

MS (Mass splicing for up to 8 primary/secondary coated fibers) | SP (Single patch for up to 2 SC or 4 LC adapters)

Splice Tray Included, quantity

2

Splices per Tray, note

8 splices (250/900 μ m) per tray

Splices per Tray, quantity

8

Dimensions

Depth

12.00 mm | 0.47 in

Height

152.00 mm | 5.98 in

Weight

0.10 kg | 0.22 lb

Width

105.00 mm | 4.13 in

Mechanical Specifications

Material Type

PBT | PET

Minimum Bend Radius, standard

15.00 mm | 0.59 in

Environmental Specifications

Environmental Space	Indoor Outdoor
Relative Humidity	93%, non-condensing
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system