

FACT[®]-WR: Fiber Wall Mountable Rack



KEY FEATURES

- **Supports all FACT[®] chassis types**, including splice-only, patch/splice, and pre-cabled units
- **Compact metal housing** with a single lockable metal door and swing handle
- **Designed for FACT[®] mounting system** without back plates
- **4 interchangeable cable inlet plates** (top, bottom, left, right) 2 blanks, 2 with various knockout holes for cable glands
- **Includes an internal cable plate** for cable separation, as a variation of different glands
- **Installer-friendly wall attachment kit** included with "hook-on and attach" brackets, mountable at top/bottom or sides
- **Integrated fiber management system** with drums for flexible patching
- **IP55 Dust- and splash-proof** construction
- **Integrated RU attachment** for 19" panels
- **FACT and RU numbering**



The FACT-WR is a compact, sealed wall-mountable rack featuring a unique physical fiber management system. Designed for use in datacenter entrance rooms, exchanges, head-ends, or customer premises, it is ideal fiber entrance rooms and vault applications where outdoor cables are spliced to indoor cables. It also serves as a small Optical Distribution Frame (ODF) for limited fiber counts.

As the successor to the FIST[®]-WR2 wall rack, the FACT-WR is fully compatible with CommScope's advanced FACT[®] chassis portfolio.

Size: 1000 mm height: accommodates up to 28 FACT elements

Dimensions and capacity

Description	Dimensions H / W / D	Capacity FACT elements	Max Capacity ports with FACT		Max Splice Capacity with FACT	
			SC	LC	12 smouv tray	Rollable ribbon
FACT-WR-28E	1000 – 840 – 330	28 FACT Elements	672 ports	1344 ports	2016	4032