760262621 | IFEB-40PPLG024-C14A-GJJNN-DE16



IFEB40, Indoor Fiber Optic Wall mount Enclosure, Splice-Patch / Splice-Patch, LC/APC Pigtails Grade B (48) and Adapters (16 duplex), patch panel(1), Single Element Slim trays (14) ANT, SE tray (1) with SE tray (1) with splitterholder (3) for 250µ splitters 1:8 (0), Feeder cable seal 4x15mm (1) and 24x7mm drop seal (2), 4-Cable drop fixation kit (6), RAL 9010

Customer entry box for OXG-Germany, **Size M, for 24 up to 31 customer connections.**

IFEB40, Indoor Fiber Optic Wall mount Enclosure, equipped for splicing LC/APC pigtails to as well the feeder cable as the drop cables.
Feeder & drop can be patched to each other on a patch panel with 16 duplex Adapters, 48 pigtails LCA/PC for 24 customer connection (minimum config) are foreseen.

Each customer connects thru 1 half of a duplex adaptor:

From feeding side: the OXG feeding fiber (can be a splitter output or direct);
From customer side: Connection to 1 of the 4 fibers in the drop cable.

Trays from top to bottom:

11 Single Element Slim trays ANT are planned to splice each 1 fiber of to 3 CUSTOMER DROP cables into 3 pigtails, the 3 other fibers of each drop cables will be spare fiber ,

2 Single Element Slim trays ANT are planned to splice the SPLITTER OUTPUTS to a pigtail for further customer connection ,

1 Single Element Slim tray ANT is planned to splice up to 12 fibers of the FEEDER: 2 fibers into the SPLITTER INPUT, the rest of the fibers into pigtails for DIRECT CONNECTIONS ,

1 Single Element tray equipped with 3 splitter holders for HOLDING 3 SPLITTERS 250µ 1:8 splitters, each fed via 1 fiber of the feeding cable.
Customer can be fed thru the splitter outputs (max 3 X 8 customers) or directly patched from feeder cable.

For cable sealing : 4x15mm and 24x7mm drop seal (2), 6 X 4-Cable drop fixation kit (6)

Product Classification

Regional Availability	EMEA
Portfolio	CommScope®
Product Type	Fiber wall box

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: October 2, 2026

Product Series	IFEB-40
Customer Restricted to	OXG

General Specifications


Functionality	Patching | Splicing
Access	Front
Adapter Ports, quantity	32
Cable Ports, quantity	4
Drop Port, quantity	48
Enclosure Color	Pure White (RAL 9010)
Front Cover Type	Hinged
Interface	LC/APC
Interface Feature	Grade B
Pigtails Included, quantity	48
Splice Tray Construction	SLE (Slim element tray for up to 12 primary coated fibers) | SE (Single Element) with splitter holder & 3 splitters 1:8 (250µm)
Splicing Type	ANT
Splicing Type, Supported	Single fusion
Splitter Type	1 x 8
Splitter, quantity	3

Dimensions

Height	425 mm | 16.732 in
Height, with cover	500 mm | 19.685 in
Width	295 mm | 11.614 in
Depth	145 mm | 5.709 in
Volume	14.1 L

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: October 2, 2026

Dimension Drawing



©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: October 2, 2026

Representative Image



Environmental Specifications

Installation temperature	-5 °C to +45 °C (+23 °F to +113 °F)
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Indoor
Flammability Rating	UL 94 V-0
Qualification Standards	IEC 60529, IP50 | IEC 61753-1 Ed.2 2018 - Category C

Packaging and Weights

Included	Box (1) | Drop Seal, 24x7 (2) | SLE ANT trays (14) | SE tray (1) | Feeder Seal, 4x15 (1) | LC/APC duplex adapters (16) | LC/APC Pigtails Grade B (48)

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: October 2, 2026

Packaging quantity	1
Packaging Type	Box

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: October 2, 2026