



FIST™ GCOG2 Fiber Optic Splice Closure, Heat Shrink Cable sealing, size DD, no pre-installed fiber trays, 24 ports

Product Classification

| | |
|------------------------------|-----------------------------------|
| Product Type | Single-ended, round fiber closure |
| Regional Availability | EMEA |
| Product Series | FIST-GCOG2 |

General Specifications

| | |
|--|---------------|
| Splicing Type, Supported | Single fusion |
| Color | Black |
| Network Area Type | Distribution |
| Package, quantity | 1 |
| Packaging Type | Box Carton |
| Splice Tray Included, quantity | 0 |
| Splicing Capacity, Single Splice, 2 fibers, maximum | 24 |

Dimensions

| | |
|-------------------------------------|--------------------|
| Main Cable Diameter, maximum | 21.00 mm |
| Weight | 5.50 kg 12.13 lb |

Mechanical Specifications

| | |
|------------------------------------|--------------------------------|
| Cable Sealing Type | Compressed gel |
| Cable Entry Drop Port Style | Round |
| Cable Entry Main Port Style | Round |
| Cable Ports, quantity | 24 |
| Closure Sealing Type | Dome-to-base clamp with O-ring |
| Closure Style | Single-ended |
| Material Type | Impact-resistant polymer |
| Mount Type | Pole Strand Wall |

Environmental Specifications

| | |
|-------------------------------|--------------------------|
| Environmental Space | Below ground Buried |
| Qualification Standard | IEC 61300, 5 m waterhead |

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant