


Technical datasheet for:

EZA-t 12 mini



General data

Item	Sealing element	
Description	The tensile, gas and watertight sealing elements EZA-t mini are reusable and are suitable for sealing speedpipe ground with an outer diameter of 12 mm with cable / fiber optic cable. For the proper function of the EZA-t mini a min. wall thickness of 2.0 mm is required. Due to their compact design, they have been specially developed for limited space and hard-to-reach places. Due to the slotted design, subsequent installation is also possible. The different coloured rubber sealings make it easy to differentiate between the individual sealing areas. They are not suitable for direct burial.	
Package unit	50 pcs.	
Transport and storage temperature	-40 to +65	°C
Laying or installation temperature	-10 to +50	°C
Operating temperature	-40 to +65	°C

Technical data

Single part	Material	Colour
Body	POM	black
Release ring	POM	grey
Sealing	TPE	different per dimension
Claw ring	Stainless steel	
Quality	Value	Unit
Dimension	d = 21.0 ; L = 33.0	mm
Sealing range (short term / colour rubber sealing)	EZA-t 12 / 3.0-3.5 mini (grey)	mm
	EZA-t 12 / 3.5-4.0 mini (brown)	
	EZA-t 12 / 4.0-4.5 mini (violet)	
	EZA-t 12 / 4.5-5.0 mini (turquoise)	
	EZA-t 12 / 5.0-5.5 mini (black)	
	EZA-t 12 / 5.5-6.0 mini (orange)	
	EZA-t 12 / 6.0-6.5 mini (pink)	
	EZA-t 12 / 6.5-7.0 mini (red)	
Pressure	0.5	bar
Tensile strength of speedpipe	min. 120	N

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
GERMANY

Tel. +49 9962 950-200
Fax +49 9962 950-202
info@gabocom.com
www.gabocom.com

Editor: AF
Variant
Date: 12.03.2024
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.

© 2024 gabo Systemtechnik GmbH, all rights reserved

Page 1/1